

## Cable glands Progress® nickel-plated brass



### Short entry thread metric

#### Type approval: Progress MS

- Two-piece sealing insert
- not overall length insulated

|                                    |                              |
|------------------------------------|------------------------------|
| Article no:                        | 1000.75                      |
| E-No:                              | 121069928                    |
| EAN:                               | 7611614104621                |
| Material                           | Nickel-plated brass          |
| Seal                               | TPE                          |
| O-ring                             | NBR                          |
| Operation temperature              | -40°C / +100°C               |
| Strain relief                      | Version A acc. to EN 62444   |
| Protection class                   | IP 68 (up to 10 bar) / IP 69 |
| NEMA Type rating                   | 4X                           |
| Entry thread                       | M75x1.5                      |
| Clamping range with insert min.    | 50.0 mm                      |
| Clamping range with insert max.    | 56.0 mm                      |
| Clamping range without insert min. | 56.0 mm                      |
| Clamping range without insert max. | 63.0 mm                      |
| Wrench size                        | 80 mm                        |
| Dimension H                        | 38 mm                        |
| Thread length L                    | 11 mm                        |
| UL - clamping range                | 49.8-55.7 mm                 |
| Dispatch                           | 1                            |

Available with sealing inserts conformity with EN 45545 / NFPA 130. When placing an inquiry, prefix the article number by the capital F.