

## Cable glands Progress® nickel-plated brass



### Short entry thread metric

#### Type approval: Progress MS

- One-piece sealing insert
- overall length insulated

|                       |                              |
|-----------------------|------------------------------|
| Article no:           | 1060.10.040                  |
| E-No:                 | 121077208                    |
| EAN:                  | 7611614105154                |
| Material              | Nickel-plated brass          |
| Seal                  | TPE                          |
| O-ring                | NBR                          |
| Operation temperature | -40°C / +100°C               |
| Strain relief         | Version A acc. to EN 62444   |
| Protection class      | IP 68 (up to 10 bar) / IP 69 |
| NEMA Type rating      | 4X                           |
| Entry thread          | M10x1.5                      |
| Clamping range min.   | 3.0 mm                       |
| Clamping range max.   | 4.0 mm                       |
| Wrench size           | 13 mm                        |
| Dimension H           | 15 mm                        |
| Thread length L       | 5 mm                         |
| Note                  | 1                            |
| UL - clamping range   | 4.0-4.0 mm                   |
| Dispatch              | 50                           |

1 = Metric coarse-pitch thread (with VDE test report)

Available with sealing inserts conformity with EN 45545 / NFPA 130. When placing an inquiry, prefix the article number by the capital F.